

**SONALIKA**  
LEADING AGRI EVOLUTION

SONALIKA  
**SIKANDER**

**RX 42**



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

**KING OF FIELDS**

**CHAMPION ON ROADS**

Unmatched Power - Can Operate  
0.33m Bigger Rotavator W.R.T.  
other brands

Easy lifting of trolley with company  
fitted DCV (Trolley Pressure Pipe)

Highest Torque - 197 Nm

Maximum Speed - Best speed in  
category 34.07 km/h

Fingertip control hydraulics -  
Uniform depth - better yield

Best Stability - Zero front  
end lifting.



**WORLD'S NO. 1**

**HEAVY DUTY TRACTOR RANGE**

For more information please contact :

TOLL FREE NO. **1800 102 1011**

[www.sonalika.com](http://www.sonalika.com)



SABSE **KAM DIESEL** MEIN

SABSE **ZYADA TAAQAT** AUR **RAFTAAR**

PARAMETERS	SWARAJ 843 XM	MF 241 DI MS	M&M 475 DI MKM BP	JD 5042 D	RX-42 HDM SIKANDER
Engine Power (cc)	2730	2500	2730	2940	<b>2891</b>
Maximum Torque (Nm)	166.7	158.2	159.8	144.9	<b>197</b>
Maximum Speed (km/h)	29.3	29.3	28.34	30.88	<b>34.07</b>
Hydraulic Lift Capacity (kg)	1200	1700	1500	1600	<b>1800</b>
Gear Oil Changing Period (Hrs)	1600	600	1200	1250	<b>1800</b>

**Powerful Engine**

More power to operate heavy agriculture equipment's and Haulage work

**Highest Backup & Maximum Torque**

Zero RPM drop on heavy applications - More diesel saving

**Best Speed Combinations**

Better productivity per hour - More earning

**Best Lifting Capacity**

Easy to operate with heavy loads

**Heavy Duty Parts**

More saving due to lowest maintenance cost



Note: Above details are as per respective CFMTTI Budni reports / web information from manufacturers, Data for strictly internal usage only.

**DI-42 RX HDM SIKANDER SPECIFICATION**

Model	DI-42 RX HDM S3
Drive	2WD
Engine	4 Stroke, Direct Injection, Water Cooled, Diesel Engine
No of Cylinder/ Displacement	3 / 2891cc
H.P. Category	42
Rated Engine Speed	1800
Transmission Type	Constant Mesh
Speed Range km/h	2.46 - 34.07
PTO	540
Clutch Type	Single Clutch / Dual Clutch
Brakes	Dry Disc / OIB
Steering Type	Mechanical / Power
Wheel Base	1970 mm / 2080 mm (with Power Steering)
Lifting Capacity	1800 kg
Front Tyre	152.4mm - 406.4mm (6.0-16)
Rear Tyre	345.44mm - 711.2mm (13.6-28)

Options Available: DI-42 RX HDM S1, DI-42 RX HDM S2, DI-42 RX HDM S3

**MANUFACTURED IN THE WORLD NO.1 PLANT**



\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

**WORLD'S NO. 1**

**HEAVY DUTY TRACTOR RANGE**

**International Tractors Limited**

Head Office & Plant: Village Chak Gujran, P.O. Piplanwala- 146022 Jalandhar Road, Hoshiarpur (Pb.) - INDIA | Phone: +91-1882-522220, 522221 | Fax: +91-1882-522222

Marketing Office: C-133 A, Sector-2, Noida (UP) - 201301 | Phone: +91-120-4095860

www.sonalika.com | welcome@sonalika.com | https://twitter.com/Sonalika\_India | https://www.facebook.com/SonalikaTractorsOfficial | https://www.youtube.com/channel/UCY\_A8yslhL03FUbmtRsRCxQ

LESSR42X2319